

VACUUM SINGLE CHAMBER

Models | 400 | 450A | 450T | 550A | 580A

HEAVY-DUTY

This high-quality, user-friendly, and easy to clean machine integrates heavy-duty parts, thereby providing great reliability.

PERFORMANCE

This model is designed to package large volumes of oversized products. The modified atmosphere packaging (MAP) option extends the shelf life of food and reduces the need for preservation chemicals.

CERTIFIED

The Sipromac vacuum packaging machines are ETL LISTED, CSA certified and conform to USL STD.

WHY SHOULD YOU VACUUM PACK ?

- 1 To reduce spoilage by removing air from the package resulting in much longer shelf life;
- 2 To prevent dehydration;
- 3 For ease of handling;
- 4 To slow down oxidation;
- 5 To protect against external contamination.



MODELS 400, 450A AND 450T

		400	450A	450T
SEAL BARS	Length	A 19.1" / 485 mm	19.1" / 485 mm	19.1" / 485 mm
	Qty	2	2	2
	Distance between	B 23" / 584 mm	23" / 584 mm	22" / 559 mm
CHAMBER DIMENSIONS	Height	9.5" / 241 mm	9.5" / 241 mm	8" / 203 mm
BUSCH PUMP	Std.	40 m ³ 2.0 HP	40 m ³ 2.0 HP	20 m ³ 2.0 HP
MACHINE DIMENSIONS	Width	E 30.5" / 775 mm	30.5" / 775 mm	30.5" / 775 mm
	Depth	F 32" / 813 mm	32" / 813 mm	28" / 711 mm
	Height	G 44" / 1,118 mm	44" / 1,118 mm	21" / 533 mm
POWER SUPPLY		208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz	120 V / 1 pH / 60 Hz
MICROPROCESSOR		MC-05	MC-40	MC-40

VACUUM SINGLE CHAMBER

Models | 400 | 450A | 450T | 550A | 580A




MODELS 550A AND 580A

		550A	580A
SEAL BARS	Length	A 26.0" / 660 mm	33.5" / 855 mm
	Qty	2	2
	Distance between	B 23.25" / 591 mm	36.75" / 933 mm
CHAMBER DIMENSIONS	Height	8" / 203 mm	8" / 203 mm
BUSCH PUMP	Std.	63 m ³ 3.0 HP	165 m ³ 7.5 HP
MACHINE DIMENSIONS	Width	E 31" / 787 mm	45.25" / 1,153 mm
	Depth	F 36" / 914 mm	46.5" / 1,183 mm
	Height	G 47" / 1,194 mm	43.75" / 1,113 mm
POWER SUPPLY		208-220 V / 3 pH / 60 Hz	208-220 V / 3 pH / 60 Hz
MICROPROCESSOR		MC-40	MC-05

2 SEAL BARS

MC-40

MC-05



BASIC FEATURES

- Single chamber
- Stainless steel construction
- Twin seal element – Double seam band
- Vacuum sensor - Vacuum level controlled in percentage directly with Microprocessor (except model 400)
- Filler plates
- Cover latch
- Wheels (stainless steel)
- Rear panel
- Crate
- Certification; ETL listed C & US (CSA & UL) (except model 400)

OPTIONAL FEATURES

- Electric cut-off - Two wire seal system which outside wire cuts off excessive part of bag
- Bi-active seal - Sealing from top and bottom for thick pouches and aluminum bags on models 550A and 580A
- Gas injection system (MAP) - For fragile products, presentation and extending shelf life (except model 400)
- Air regulator – Regulated air pressure in the seal bars bladders with compressed air (not included) (except model 400)
- Adjustable venting system - Controlled decompression of the vacuum chamber
- 12" (305 mm) chamber lid on models 550A and 580A
- Vacuum pump sizes
- Inclined stainless steel filler plates for liquid
- Silencer
- Other voltages available
- Heated control box for microprocessor
- Service kit for standard maintenance

All features are subject to change without notice.